



**气缸套件/Assembly kits for pneumatic cylinder**

型号/Model	产品/Product	规格/Specification	型号/Model	产品/Product	规格/Specification	型号/Model	产品/Product	规格/Specification
DNC SI SC/SU MA8432 MA MAL SDA SG CQ2 TN ACCESSORY SWITCH KITS JAC/JADHR	DNC 套件/Kits (ISO6431 &VDMA 24562)	缸径/ Bore size: φ 32,40, 50,63,80,100	SI 套件/Kits (ISO6431)	缸径/ Bore size: φ 32,40,50, 63,80,100,125, 160,200, 250,320	缸径/ Bore size: φ 32,40,50, 63,80,100,125, 160,200, 250,320	SC 套件/Kits	缸径/ Bore size: φ 32,40,50, 63,80,100,125, 160,200, 250,320	缸径/ Bore size: φ 32,40,50, 63,80,100,125, 160,200, 250,320
	MAL 套件/Kits	缸径/ Bore size: φ 16,20, 25,32,40	MA 套件/Kits	缸径/ Bore size: φ 16,20, 25,32,40	缸径/ Bore size: φ 16,20, 25,32,40	SDA 套件/Kits	缸径/ Bore size: φ 12,16,20, 25,32,40,50, 63,80,100	缸径/ Bore size: φ 12,16,20, 25,32,40,50, 63,80,100

如果您需要不同颜色的气缸端盖, 请告诉我们, 我们将根据您的要求来制作。  
If you need the different color for cylinder cover, pls inform and we can produce according to your requirement.

**气缸管及活塞杆/Tube and piston rod for pneumatic cylinder**

型号/Model	产品/Product	规格/Specification	型号/Model	产品/Product	规格/Specification
DNC 方形管/ Square Aluminum Tube		缸径/Bore size: φ 32,40,50, 63,80,100,125	SI 米字形管/ Mickey Mouse Aluminum Tube		缸径/Bore size: φ 32,40,50, 63,80,100, 125,160,200
MA MA8432 不锈钢管 (高精度) Stainless Steel Tube (High precision)		缸径/Bore size: φ 8,10,12, 16,20,25,32,40	SC,MAL 圆形管/ Round Aluminum Tube		缸径/Bore size: φ 16,20, 25,32,40,50,63, 80,100,125,160, 200,250,320
活塞杆 45号钢 (镀铬) Piston rod (45# Steel Chromi- plated)		Bore size: φ 6,8,10,12,16,20,25,32,40,45, 50,60,70,等/etc.	SDA 铝管/ Aluminum Tube		缸径/Bore size: φ 12,16,20,25,32, 40,50,63,80,100 通过我们提供的SDA铝管是未氧化的。 如果您需要氧化的铝管, 请特别说明。 因为价格不同。 Normally we provide SDA un-oxidized aluminum tube, if you need that with oxide, pls be specified, because price is different.

**特殊气缸/Special Cylinder**

告诉我们您的详细需求JXPC承诺50天之内完成您的特殊产品。  
We are glad to finish all kinds of special cylinder in 50 days according to customers' requirement.



**JAC/JAD系列缓冲器/JAC/JAD Series Shock Absorbers**

● 订购码/Ordering Code

**JAD - 25 - 25 - 1 - N**

- 系列代码: JAC: 多孔固定式, JAD: 可调节式, JACD: 多向缓冲式 Series
- 轴套外牙: Bushing Outer Thread
- 行程: Stroke 6-150mm
- 撞击速度: 1.高速, 2.中速, 3.低速 Impact speed
- 缓冲帽: 空白带缓冲帽, N: 不带缓冲帽 Blank with buffer cap, N: Without buffer cap

● 规格/Specifications

型号/Model	行程/Stroke	最大吸收能量 Max.Absorb Energy (NJM)	小时吸收能量 Max.Absorb Energy/Hour (NJM)	最大有效能量/Max.Effective Mass(kg)			最高撞击速度/Max.Impact Speed (m/s)		
				1	2	3	1	2	3
JAC-0806	6	2	7,00	0.5	2	6	2	1	0.5
JAC-1005	5	3	10,800	1	3	7	3	1.5	0.8
JAC-1008	8	4	14,400	2	4	9	3	1.5	0.8
JAC-1210	10	5	18,000	5	10	30	2	1.5	0.8
JAC-1412	12	15	36,000	8	50	100	3	1.5	0.8
JAC-1416	16	20	40,000	10	70	150	3	1.5	0.8
JAC-1420	20	25	48,000	12	80	160	3	1.5	0.8
JAC-2020	20	40	48,000	30	200	700	3.5	2	1
JAC-2030	30	50	54,000	30	200	700	3.5	2	1
JAC-2050	50	60	66,000	60	400	1200	3.5	2	1
JAC-2525	25	80	60,000	200	800	1500	4	2.5	1
JAC-2540	40	120	84,000	300	1200	2000	4	2.5	1
JAC-2550	50	98	98,000	15	40	160	4	2.5	1
JAC-2580	80	150	127,500	20	50	200	4	2.5	1
JAC-3660	60	250	125,000	400	1500	2400	4	2.5	1
JAC-2030	30	45	54,000	40	300	900	3.5	2	1
JAC-2035	35	52	64,400	40	200	650	3.5	2	1

工作温度: -10~80°C / Working Temperature: -10~80°C

型号/Model	JAD 系列/Series									
	JAD-1410	JAD-1415	JAD-2016	JAD-2025	JAD-2525	JAD-2530	JAD-2540	JAD-2550	JAD-2580	JAD-2580
行程/Stroke	10	15	16	25	25	30	40	50	80	80
最大吸收能量/Max.Absorb Energy(NM)	20	22	25	39	85	95	100	98	150	150
小时吸收能量/Max.Absorb Energy/Hour(NM)	24,000	26,400	32,000	39,000	51,000	57,000	64,000	98,000	127,500	127,500
最大有效能量/Max.Effective Mass(kg)	80	120	200	312	400	480	700	720	800	800
最高撞击速度/Max.Impact Speed(m/s)	3.2	3.2	3.6	3.6	3.6	3.6	3.6	4.2	4.2	4.2

  

型号/Model	JAD 系列/Series									
	JAD-3625	JAD-3650	JAD-4225	JAD-4250	JAD-4275	JAD-64050	JAD-64100	JAD-64150	JAD-64150	JAD-64150
行程/Stroke	25	50	25	50	75	50	100	150	150	150
最大吸收能量/Max.Absorb Energy(NM)	150	300	260	500	750	12,000	24,000	36,000	36,000	36,000
小时吸收能量/Max.Absorb Energy/Hour(NM)	90,000	108,000	130,000	155,000	187,000	1,560,000	1,920,000	2,520,000	2,520,000	2,520,000
最大有效能量/Max.Effective Mass(kg)	1,400	1,400	3,000	4,000	6,000	12,727	18,181	23,636	23,636	23,636
最高撞击速度/Max.Impact Speed(m/s)	3.2	4.8	3.6	4.8	4.8	1.6	1.6	1.6	1.6	1.6

工作温度: -10~80°C / Working Temperature: -10~80°C

● HR 系列油压稳速器/Series speed regulator



● 订购码/Ordering Code

**HR - 30 - F**

- 系列代码: HR: 可调节式油压稳速器 Series
- 行程: Stroke 15-100mm
- 支架: Bracket